


REPAIR WAX

PERGO ORIGINAL LAMINATE® **PERGO** WOOD PARQUET® **PERGO** VINYL PLANKS & TILES®

<u>Order code</u>	<u>Type</u>	<u>Picture</u>	<u>Packaging</u>
PGREPAIR	REPAIR WAX		12 pc = 1 pack

Product description

Repair kit for minor and medium-severe damaged laminate, vinyl or parquet floors (flat surfaces and edges).

- Order code: PGREPAIR
- Packaging quantity: 1
- Contents: 1 melter, 1 cleaning comb, 1 grey sanding pad, 1 green/white pad, 7 wax blocks and 1 instruction manual. Batteries not included.

Characteristics

- Mixture of mineral waxes colored with earth and oxide dyes.
- Good adhesion properties.
- Colour shades can be mixed together during melting.
- Can be easily stripped off by means of the special fillers application, a chisel or the metal planer.
- Good elasticity (no development of cracks).

Applications

Pergo® laminate, Pergo® Vinyl and Pergo® Parquet stand for quality. The laminate floor consists of a hard core of a high-quality HDF board, which makes the Pergo® floor extremely wear and impact resistant. Pergo® is also a laminate with an exceptionally resistant wear layer.

Pergo® Parquet floors are composed of 100% natural materials and treated with lacquer or oil for optimal protection.

When a very sharp object falls on the floor from a fair height (e.g. the point of some scissors), it is sometimes unavoidable for the floor to sustain slight damage. The Pergo® Repair Wax can be used to repair the light damaged area.

Specifications

- **MATCHING REPAIR:** The Pergo® Repair Wax offers a matching solution for every Pergo® Laminate, Vinyl and Parquet floor. This enables you to optimize the colour to the shade that best matches the damaged plank.

REPAIR WAX

- **EASY AND FAST:** The room looks nicely finished, without having to change the damaged plank.
- **A COMPLETE REPAIR KIT:** All the elements needed for repairing every Pergo® floor are available in one and the same kit.
- **SHELF LIFE:** unlimited (stored at room temperature, in unopened original container)
- **SOFTENING POINT:** 76°C (ISO 2207) – Dropping point: 81°C (DIN 51801)

Safety Precautions

The product is neither subject to the Hazardous Freight Regulations nor to the Dangerous Substances Directive.

1). Preparation:

Proper preparation is important. Clean the damage on the floor first and make sure it is free from dust, oil, wax and grease.

**2). Choose your colours:**

Choose your colours according to the recommendations on www.pergo.com.



REPAIR WAX**3). Melt and mix****4). Filling****5). Levelling:**

Use the sharp edge of the filler to scrape off excess material.



REPAIR WAX

6). Precise adjustment:

For a precise adjustment of the wood pattern you can scratch the area to be restored with a pointed item and fill it with a darker colour.

**7). Degrease using the grey sanding pad****8). Adjust the gloss level:**

Use the green side of the green/white pad to make the area more glossy. Use the white side to make it more matt.



For more information, see www.pergo.com.